

# QUATTRO



## MIXING PUMP FOR PREMIXED MATERIALS

### OPTIONAL ACCESSORIES:



**Ref. 0198026**  
Silo conveying system for freefall silos.



**Ref. 0198032**  
Silo conveying system for pressure silos.



**Ref. 45502**  
Inflation hood.

### TECHNICAL DATA:

	ref. 0198061 three phase	<b>NEW</b> ref. 0198063 single-three phase
Output	5 to 45 l/min *	0 to 45 l/min *
Pumping distance	Aprox. 40 m *	Aprox. 40 m *
Pumping height	Aprox. 20 m *	Aprox. 20 m *
Tension	380 V	220V and 400V
Pumping pressure	40 bars max.	40 bars max.
Main motor power	5'5 Kw	4 Kw
Feeding motor power	0'55 Kw	0'55 Kw
Air compressor	250 l/min, 5 bar, 0'9 kW	0'75 kW-220 V-170 l/min
Nec. water pressure	3 bars	3 bars
Electric connection (5x2,5mm <sup>2</sup> )	400 V-50Hz 3 P+N+T 32 A/6h	400 V-50 Hz, 3P+N+T 32 NGh 220 V-50Hz 25 A
Dimensions LxWxH (mm)	1.100 x 660 x 1.455	1.100 x 660 x 1.455
Weight	215 kg	205 kg
Filling Height	870 mm	870 mm
Water Pump	0'37 kW - 400 V (3ph)	0'37 kW - 220 V (1ph)

\* depends on material quality, hose length and diameter and pumping height.

## FEATURES:

- Mixing pump for premixed material with large hopper capacity.
- Simple and robust.
- Mixing tube can be inclined without loss of dry material to change stator and rotor.
- Machine can be filled with premixed material from bags or from silos.
- The worm pump transports the material through hoses to the spraygun where it is sprayed on the surface with compressed air.
- In case of insufficient water pressure the electric control stops the machine.
- The electric control box is sealed to avoid damage from dust or water.

## ADVANTAGES:

- Fits through all standard doors. 660 mm wide. Narrowest machine on the market.
- Machine can be taken in to parts within minutes for easy transport.
- Can be carried in small vehicle when taken to parts.
- Equipped with 4 wheels makes transport on construction site easy.
- Easy to work and maintain.

## SERIAL EQUIPMENT:

- Automatic stopping system.
- Compressor 250 l/min.
- Water pump.
- Tool Kit.
- Spray gun.
- Mixing shaft.
- Cleaning tools.
- Warranty Certificate.
- CE Certificate.
- Parts book and manual.

Always ask for original tools and spare parts.  
Due to continuous improvement and development  
all machines can be modified without previous advice.

## RECOMMENDED EQUIPMENT (on order):

- Stator and rotor.
- Mortar hose.
- Air hose.
- Electric cable 5 x 2,5 mm.
- Electric cable 3 x 2,5 mm.
- Ref. 38201 Water suction hose -5 m- with valve.
- Ref. 31860 Water barrel 220 l with lid and valve.



Stator fixing system.



Mixing tube safety system.



Low filling height.



Transport handles.



Easy to take to parts for easy transport.

## OUR DISTRIBUTOR: