

MIXER LIGHT

PLASTER

Continuous mixing pump | reference : 915000200A



Extremely compact continuous mixing pump with reduced weight and size. Easy to disassemble into 3 sections to ease transport.

It can spray slurry products such as plaster-, lime- and cement-based surface coatings, etc.

This pump is also ideal for filling joints, applying adhesives, resurfacing products, and interior and exterior finishes.

TECHNICAL DATA

Hopper capacity	70 L
Power supply	230 V - 50 Hz
Thermal protection	yes
Gear motor	2.2 KW
Variable speed	yes
Integrated compressor (cat. C5)	8021022600
Water pump	yes
Flow meter	yes
Water shortage safety device	yes
Spraying flow rate	8 to 26 L/min*
Max. distance	40 meters*
Loading height	102 cm
Dimensions (l x w x h)	100 x 59 x 159 cm
Weight	130 kg

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Cleaning shaft
- 25x37 15 LM spray hose with couplings
- 13x19 16 LM air hose with GEKA coupling
- 19 x 26 40 LM water hose with GEKA coupling
- 20 LM neoprene 3x4 power cord with plug
- Mixer full spray lance made from aluminium tubing
- Adapter + GEKA coupling
- T - handle wrench
- Tool bag
- Compressor unit

MIXER[®]