

OPTIMIX 20

THREE-PHASE - 5.5 KW

Spraying machines for slurry products | reference : 912000250A



Versatile machine ideal for spraying conventional, pre-mixed surface mortars, special products and cement screed.

This machine is compatible with any product with a grain size not exceeding 6 mm, with a drying time of minimum 60 min and a density enabling it to flow through the hose.

TECHNICAL DATA

Hopper capacity	80 L
Power supply	400 V - 50 Hz
Motor power	5.5 kW
Compressor flow rate	250 L/min
Variable speed	yes
Compressor motor power	0.75 kW
Spraying flow rate	0 to 50 L/min
Max. spraying distance	60 meters*
Max. pressure	3.5 bar
Max. grain size	6 mm
Integrated compressor (cat. C5)	9002005000
Dimensions (l x w x h)	140 x 70 x 81 cm
Weight	185 kg

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Two 35x50 10 LM spray hoses with 1 1/4 couplings
- Classic spray lance
- 50 LM neoprene 4x2.5 power cord with plug
- 13x19 21 LM air hose with GEKA coupling
- Maintenance kit

MIXER[®]