



Application areas:

- Special foundation engineering, Tunnelling (bored pile, cut-off wall, jet grouting)
- Biogas production

Pumping of:

- Bentonite slurries, drilling fluids, sealing wall slurries, groundwater, mortar, slurries, dirty water; cement, fly ash or other solid-containing slurries
- Return suspensions
- Slurries
- Biomasses, Press water

Technical Data / Performance Data *

Flow rate speed n1	max. 6	m³/h
Flow rate speed n2	max. 12	m³/h
Discharge pressure	max. 6	bar
Suction lift	max. 8	m
Solids grain size	max. 16	mm
Medium temperature	50	°C
Nominal diameter of hose	50	mm
Suction connection	Storz C	2" standard coupling DIN 14307, alternatively 2" AG, flange DN50 PN16
Pressure connection	Storz C	2" standard coupling DIN 14307, alternatively 2" AG, flange DN50 PN16
Power connection	CEE-plug	16 A, 5-pole
Power input	4,5	kW
Voltage	400	V; 50 Hz
Dimensions	0,63 x 0,69 x 1,12	m (L x W x H)
Weight	approx.160	kg

)* The stated values are approximate values and refer to the pumping of water with 18 ° C. Conditionally by abrasion of the hose pump, unfavourable suction, pressure conditions and influence of viscosity of the pumping medium may differ the actual performance data from the specified data.

Features:

- ✓ **Pump housing** with housing cover in standard steel version
- ✓ **Moveable pump frame** (rubber tires)
- ✓ **Pump drive** with rotor bearing and flange bearing in the housing cover
2 flow rates by 2 different conveying speeds
- ✓ **Pump rotor** with rotatable mounted pressure rollers
- ✓ **Steel pressure roles** with roller bearings and eccentric adjustment
(wear compensation of hose pump)
- ✓ **Electrical function and power control** with the following display and control elements:
 - Main switch ON/OFF
 - Pump ON/OFF
 - Selector switch reversing operation (forward/backwards)

Accessories (not included in delivery):

- Suction filters / suction tubes
- Suction and discharge hoses
- Suction and pressure connections in Storz or Perrot
- Frequency converter