



Application areas:

- Anchor injection
- Grouting
- Cavity filling
- Micro tunnelling
- Ground injection
- Bentonite lubrication

Mixing of:

- Cement slurries
- Anchor grout
- Bentonite slurries
- Filling material for peripheral sealing
- Insulation slurries
- Fly ash slurries

Technical Data / Performance Data *

Mixing capacity (20 batches/h)	5,6	m ³ /h
Effective mixer volume	280	l
Mixing water minimum	90	l
Mixer filling level (bag loading)	870	mm
Buffer tank volume	560	l
Water tank capacity	250	l
Flow rate	0 - 210	l/min, continuously adjustable
Discharge pressure	max.100	bar, continuously limited
Solids grain size	max. 2	mm
Pressure connection	1 1/4"	IG
Water connection	Storz C	2" standard coupling DIN14307, max.6 bar; or Geka-claw coupling
Cleaning connection	DN 25	Geka-claw coupling
Power connection	CEE-plug	63 A, 5-pole with phase inverter
Power input	approx. 31	KW
Voltage	400	V; 50 Hz
Dimensions	2,04 x 2,17 x 2,4	m (L x W x H)
Weight	approx. 2100	kg

)* The specified performance data are non-binding values that differ significantly depending on dosing, mixing and discharge times.

Features:

- ✓ **Batch mixer** 280 l capacity (colloidal mixer); fast running colloidal mixer; debagging grid with safety-end switch; adjustable filling bar for rough water level indication and water dosage; 3-way valve in the mixer-forced circulation; mixing tank draining
- ✓ **Agitator tank** 560 l capacity; slow running agitator; inclined tank bottom for better tank draining, tank wall with cleaning opening; tank lid with inspection port and safety-end switch
- ✓ **Double plunger pump** vertically arranged;
- ✓ automatic ball valves (inlet and exhaust valves)
- ✓ **Water tank** 250 l capacity; visual level indicator; automatic filling control
- ✓ **Water dosage** by manually operated ball valve
- ✓ **Separate connection** for cleaning hose including stopcock
- ✓ **Pump suction pipe** with suction filter
- ✓ **Pump pressure pipe** with 2 lubricated high-pressure ball valves (1 x pressure relief for agitator tank, 1 x pressure port plunger pump) pressure pipe with pressure transmitter and visual pressure indicator (manometer 100 mm)
- ✓ **Hydraulic aggregate** with:
 - variable pump and fixed displacement pump
 - visual oil level indicator
 - return filter including visual contamination indicator;
 - oil minimum guard
 - venting nozzles
 - hydraulic control block with 2 hand wheels (1 x continuous adjustment of pump flow rate, 1 x continuous limiting of pump discharge pressure)
 - oil cooler
- ✓ **Steel frame** with working platform; central lifting eye; suitable seats for forklift and pallet truck handling; lifting eyes for transportation lock
- ✓ **Electrical function and power control** with the following display and control elements:

- Main switch ON/OFF	- Emergency-off-button
- Mixer ON/OFF	- Phase-control
- Pump ON/OFF	- Combined fault display
- Agitator ON/OFF	- Operation mode switch
- Diverse service counters	- Stroke counter pump
- Operation hours counter pump	- Operation hours counter mixer

Accessories (not included in delivery):

- Remote control (cable or radio)
- Electrical adjustment of flow rate (plunger pump)
- Electrical limitation discharge pressure (plunger pump)
- Digital display discharge pressure
- Optionally rinsing operation (optionally pumping of slurry or water)
- Data logging
- Grouting hoses
- Cleaning hose
- Water meter
- Mixer scale
- LED launder (with tripod)
- High-pressure cleaner

GERTEC

Maschinen- und
Anlagenbau GmbH

Ludwig-Prandtl-Str. 1
D-87448 Waltenhofen

Fax: 08303-929509-99

Phone: 08303-929509-0

Date: 08303-929509-0

info@gertec-gmbh.de

Art.No.: 42560

Date: 26.08.2016

Technical specifications

are subject to change

page 2 / 2